

Dual  
Hose

# Series F2000

• Power Rescue Tools • Hydraulics

## To handle dual 1/4" I.D. hose.

- Two swivel joint inlets and two outlet risers to handle two equal lengths of hose.
- Manual disc rewind or chain and sprocket rewind powered by an electric or compressed air motor.
- Adjustable cam-lock brake on disc rewind models is standard.
- Power rewind reels are not supplied with a brake. Optional drag brake is available. Add 3/4" to the "F" dimension shown in the chart.
- Standard inlets: 90° swivel joints, 1/4" female NPT threads.
- Standard outlets: 1/2" female NPT threads.
- Pressures to 10,500 psi (724 bar).
- Temperatures from -20°F to +225°F (-29°C to +107°C).
- Rescue tool manufacturer must be specified to determine threads and packing material required.†
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Polished stainless steel discs and sprocket with chrome frame are recommended for phosphate ester oil.



Carrying handles optional.  
(Add 2 inches to "G" dimension)  
Part No. 9955.0023



### Optional External Mounting Brackets

Part No. 9906.0027.

Add 2-1/2" to the X dimensions shown in the chart.

## PARTS DRAWING – ISO 101

Model Number For power rewind see Note 4	Hose Capacity of Reel feet m NOTE: 1 inch = 25.4 mm		Approx. Weight Disc Rewind lb. kg		Reel Dimensions*** in. mm						
	I.D. in. mm	1/4 6	NET	SHIP	A	B	E DISC	E POWER	F** DISC	F** POWER	X
	O.D. in. mm	.53 13.5									
<b>F2016-17-18</b>		<b>2/100</b>	<b>32</b>	<b>80*</b>	<b>13</b>	<b>8</b>	<b>16.5</b>	<b>19</b>	<b>17.5</b>	<b>20.5</b>	<b>11.5</b>
		2/31	15	36	330	203	419	483	445	521	292
<b>F2020-17-18</b>		<b>2/200</b>	<b>34</b>	<b>98*</b>	<b>17</b>	<b>12</b>	<b>16.5</b>	<b>19</b>	<b>21.5</b>	<b>24.5</b>	<b>15.5</b>
		2/61	15	45	432	305	419	483	546	622	394

  

**Notes:**

- Specifications subject to change.
- Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
- Weights shown in chart are for manual rewind models. Add these amounts for power rewind models (does not apply to FedEx or UPS):

	Net lbs/kg	Ship lbs/kg
<b>Electric</b>	<b>18/8.2</b>	<b>18/8.2</b>
<b>Air</b>	<b>15/6.8</b>	<b>15/6.8</b>

- When ordering power rewind models, prefix model number with:
  - A** = Air Rewind
  - E** = Electric Rewind
(Air rewind reels are supplied with control valve and 18" hose; 12v and 24v DC rewind reels are supplied with switch and solenoid.)

- Add 2-1/2" to "E" dimension and 1/2" to "G" dimension with assembly "C" roller installed in top wind (TR) position.
- Be sure to check dimensions and weights prior to ordering.
- Some roller options may prohibit the use of our molded chain guard.

**NOTICE:** A flexible connector must be used between the inlet pipe and the inlet swivel joint.

\* Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).

\*\* Swivel joints required for Hurst Systems increase the "F" dimension. Add 3/8" for power rewind and 3/4" for disc rewind.

\*\*\* X, Y indicate mounting holes. See page 2.