

Series **SS1500**

• Pest Control • Pressure Washing • Steam Cleaning

To handle single 1/4" through 5/8" I.D. hose.

- Lightweight, compact reels designed for long lengths of hose.
- Direct crank rewind is permanently attached.
- Cam-lock drag brake, spring actuated pin lock.
- Standard inlet: 90° stainless steel ball bearing swivel joint, 1/2" female NPT threads.
- Standard outlet: 1/2" female NPT threads.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Pressures to 3000 psi (207 bar).
- Temperatures from +20°F to +400°F (-7°C to +204°C).
- Consult factory for other pressures and temperatures.
- Consult factory for power version.
- 304 stainless steel construction.



Standard configuration shown with optional polished finish

PARTS DRAWING – ISO 175

Model Number	Hose Capacity of Reel feet m					Approx. Weight Crank Rewind lb. kg			Reel Dimensions*** in. mm				
	I.D. in. mm	1/4 6	3/8 10	1/2 13	5/8 16	NET	UPS/ FedEx SHIP Wt.	Freight SHIP Wt.	A	B	E	F	X
	O.D. in. mm	5/8 16	3/4 19	7/8 22	1 25								
SS1514-17-18		175	125	75	50	27	65*	62	11	6	16.5	18.5	9.5
		53	38	23	15	12	30	28	279	152	419	470	241
SS1520-17-18		350	275	175	125	29	80*	64	17	12	16.5	24.5	15.5
		107	84	53	38	13	36	29	432	305	419	622	394
SS1526-17-18		500	400	300	200	31	98*	66	23	18	16.5	30.5	21.5
		152	122	91	61	14	45	30	584	457	419	775	546
SS1530-17-18		–	500	375	275	33	110*	68	27	22	16.5	34.5	25.5
		–	152	114	84	15	50	31	686	559	419	876	648
SS1536-17-18		–	–	475	350	35	129*	70	33	28	16.5	40.5	31.5
		–	–	145	107	16	59	32	838	711	419	1029	800

Notes:

1. Specifications subject to change.
2. Upon request, reels can be supplied with drum lengths other than shown.
3. Dimension "F" is the overall length of standard model reels.
4. Manual rewind available in RT or LB configurations only.
5. Finish: Refer to page 2.
6. Be sure to check dimensions and weights prior to ordering.

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

* Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).

***X, Y indicate mounting holes. See page 2.

