

Series **SS1800**

- Pest Control • Pressure Washing
- Steam Cleaning • Washdown

To handle single 5/8" or 3/4" I.D. hose.

- Lightweight, compact reels designed for long lengths of hose.
- Direct crank rewind is permanently attached.
- Cam-lock brake, spring actuated pin lock.
- Standard inlet: 90° stainless steel ball bearing swivel joint, 1" female NPT threads.
- Standard outlet: 3/4" female NPT threads.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Pressures to 1000 psi (69 bar).
- Temperatures from +20°F to +400°F (-7°C to +204°C).
- Consult factory for other pressures and temperatures.
- 304 stainless steel construction.



Standard configuration shown

PARTS DRAWING – ISO 176

Model Number	Hose Capacity of Reel feet m			Approx. Weight Crank Rewind lb. kg			Reel Dimensions*** in. mm				
	I.D. in. mm	5/8 16	3/4 19	NET	UPS/ FedEx SHIP Wt.	Freight SHIP Wt.	A	B	E	F	X
	O.D. in. mm	1 25	1-9/32 40								
SS1816-17-18		75	50	28	80*	63	13	8	16.5	23.38	11.5
		23	15	13	36	29	330	203	419	594	292
SS1822-17-18		150	100	30	98*	65	19	14	16.5	29.38	17.5
		46	30	14	45	29	483	356	419	746	445
SS1826-17-18		200	125	32	98*	67	23	18	16.5	33.38	21.5
		61	38	15	45	30	584	457	419	848	546
SS1830-17-18		250	150	33	110*	68	27	22	16.5	37.38	25.5
		76	46	15	50	31	686	559	419	950	648
SS1836-17-18		300	200	36	129*	71	33	28	16.5	43.38	31.5
		91	61	16	59	32	838	711	419	1102	800

Notes:

- Specifications subject to change.
- Upon request, reels can be supplied with drum lengths other than shown.
- Dimension "F" is the overall length of standard model reels.
- Manual rewind available in RT or LB configurations only.
- Finish: Refer to page 2.
- Be sure to check dimensions and weights prior to ordering.

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

* Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).

***X, Y indicate mounting holes. See page 2.

