

AT1300/4300

PORTABLE CABLE REEL ON WHEELS

Model AT1300.

- Removable direct crank rewind reel.
- Adjustable Cam-lock drag brake.
- 3 conductor 45 amp collector ring is standard.
- 6-foot power source lead of 10/3 cable.
- 15 amp 3-prong straight blade (twist lock optional).
- Additional conductors available, consult factory.
- Direct offset rewind crank.

Model AT1300

For:

- Industrial Maintenance
- Construction
- Agriculture
- Broadcast
- Grounds Maintenance

ALUMINUM HAND TRUCK

Model 4300-AL. P/N 9906.0795

For portability of hose and cable reels.

- Large pneumatic tires.
- Reel permanently attached.
- Overall dimensions will vary according to the reel model used.
- Hand truck, axle and wheels shipped separately for customer installation. Specify if reel axis is perpendicular or parallel to truck axle.

Assembled 4300-AL truck with reel attached

Parts Drawing – ISO 189

| Model Number | Cable Capacity of Reel feet m. | | | | Approx. Weight lb. kg. | | Reel Dimensions inches mm. | | | | | | | |
|--------------|--------------------------------------|------------|------------|-----------|------------------------------|-----------|----------------------------------|-----------|----------|-------------|-------------|--------------|--------------|--------------|
| | GA./NO. OF CONDUCTORS | | | | NET | SHIP | A | B | C | D | E | F | G | H |
| | O.D. (in) O.D. (mm) | .53 14 | .60 15 | .69 18 | | | | | | | | | | |
| AT1300 | | 500 152 | 400 122 | 300 91 | 70 32 | 102 46 | 24.75 629 | 12 305 | 6 152 | 23.5 597 | 16.5 419 | 31.75 806 | 42.5 1080 | 14.31 363 |

Notes:

1. Specifications subject to change.
2. Truck is also sold separately. Maximum reel size dimensions when installed on hand truck:
A=32" (812.8mm), B=27" (685.8mm), E=32" (812.8mm)
3. Be sure to check dimensions and weights prior to ordering.

